

**TECHNICAL SPECIFICATIONS**

<b>MAXIMUM SUSPENDING LOAD</b> (SL = P <sub>R</sub> + P <sub>SLING</sub> + P <sub>PLAT</sub> + P <sub>LCU</sub> )	<b>SL max</b>	<b>1670</b>	<b>kg</b>
<b>RATED LOAD</b> (SUGGESTIVE)	<b>PR max</b>	<b>1200</b>	<b>kg</b>
<b>PIT DEPTH</b>	<b>PD min</b>	<b>380</b>	<b>mm</b>
<b>HEADROOM</b>	<b>HD min</b>	<b>2200</b>	<b>mm</b>
<b>PLATFORM DIMENSIONS</b>	<b>WIDTH</b>	<b>A max</b>	<b>1800</b> mm
	<b>DEPTH</b>	<b>B max</b>	<b>1500</b> mm
<b>GUIDE TYPE</b>	<b>125 x 82 x 16</b>		
<b>SAFETY GEAR TYPE</b>	<b>INSTANTANEOUS</b>		
<b>PISTON TYPE</b>	<b>Φ 90x5</b>		
<b>PUMP TYPE</b>	<b>27</b> lt/min		
<b>OIL TANK</b>	<b>T150</b>		
<b>MOTOR TYPE</b>	(230 volts 1PH)	<b>3,5</b>	<b>KW</b>
	(400 volts 3PH)	<b>3,0</b>	<b>KW</b>
<b>CAR SPEED</b>	<b>V max</b>	<b>0,15</b>	<b>m/s</b>
<b>CAR TRAVEL</b>	<b>TR max</b>	<b>9.000</b>	<b>mm</b>
<b>NUMBER OF STOPS</b>	<b>max</b>	<b>4</b>	
<b>DOORS TYPE</b>	<b>SEMI-AUTOMATIC</b>		

